

GELEN

PRODUCT BROCHURE

STE SERIES

INCLINED SCREENS

CIRCULAR MOTION. CONSISTENT CUT.

RELIABLE PERFORMANCE FROM THE COARSEST TO THE FINEST SEPARATIONS.

Two-bearing circular-motion screens with the shaft on the centre of gravity, so the whole deck moves the same way and the cut is the same from feed end to discharge. Fourteen models from 1.0 × 2.0 m to 2.4 × 7.0 m, in two, three or four decks, dry or wet.

10

MODELS IN THE SERIES

4

DECKS

2.4 × 7.0 m

LARGEST DECK

37 kW

MAX. INSTALLED POWER

APPLICATIONS


AGGREGATE SIZING

SCALPING AFTER PRIMARY

WET SCREENING & RINSING



SAND CLASSIFICATION

MINING




FROM THE MANUAL

Counterweight assembly — sets the stroke



Counterweight assembly — the eccentric mass on the exciter shaft sets the stroke.



DESIGN

ANATOMY OF AN STE.

A screen is a spring-mounted box that shakes. Everything in the STE is about making that box stiff, the shake precise, and the media easy to change.

- | | |
|--|--|
| <p>1 Centre-mounted exciter
Shaft with counterweights at the centre of gravity gives a true circular motion over the whole deck. Stroke is adjusted by the counterweights.</p> | <p>4 Lined feed box
Replaceable liners where the feed lands, and a lifting lug at each corner of the body.</p> |
| <p>2 Two to four decks
Deck frames bolted, not welded, so a deck can be added or the deck angle changed on site.</p> | <p>5 Discharge lips
Bolted, replaceable discharge lips on every deck; spray bars fit above them for wet screening.</p> |
| <p>3 Huck-bolted side plates
Stress-relieved side plates with bolted stiffeners and no welds in the vibrating structure.</p> | <p>6 Any screening media
Wire mesh, polyurethane, rubber or perforated plate on bolted tension rails, changed from the deck.</p> |

Versatile


- Dry, wet, washing and rinsing configurations
- Stroke, angle and speed adjustable to the application
- Two, three or four decks on the same body

Built to last

- Stress-relieved, huck-bolted side plates
- Heavy exciter bearings with grease or oil lubrication
- Replaceable liners on the feed box and discharge lips

Easy to maintain

- Media changes from the deck, no crane needed
- Bolted deck frames and cross members
- Standard drive and bearing families across the range




INCLINED SCREENS - STE SERIES

MODEL	WIDTH mm	LENGTH mm	2-DECK kg	3-DECK kg	4-DECK kg	POWER kW
STE2470	2400	7000	14,500	—	—	30
STE2470	2400	7000	—	16,900	19,600	37
STE2460	2400	6000	12,600	—	—	22
STE2460	2400	6000	—	15,400	18,500	30
STE2060	2000	6000	10,500	—	—	18.5
STE2060	2000	6000	—	13,700	14,600	22
STE2050	2000	5000	11,400	—	—	15
STE2050	2000	5000	—	12,200	13,800	18.5
STE1650	1600	5000	8,100	8,800	9,500	15
STE1640	1600	4000	6,600	7,000	—	11
STE1240	1200	4000	4,200	4,700	5,200	7.5
STE1030	1000	3000	2,300	2,500	—	5.5
STE1025	1000	2500	2,100	—	—	4
STE1020	1000	2000	1,550	—	—	3

Values are nominal and depend on feed material, gradation and moisture. Metric units; the Products Catalogue carries the imperial edition.




FROM THE MANUAL



STE exciter — shaft, counterweights, bearings and housings.

ONE SERIES. THE WHOLE RANGE.

From the STE1020 for a small sand line to the STE2470 four-deck at 2.4 × 7.0 m for a high-capacity aggregate plant.



SETTING THE MACHINE

- Stroke — set by adding or removing counterweights on the exciter shaft.
- Inclination — 15° to 25°, set at the support frame; steeper for coarse, flatter for fine cuts.
- Speed — set at the drive; higher speed for fine screening, lower for scalping.

HOW TO CHOOSE

- Deck area follows from feed rate and cut size: about 1 m² per 25–35 t/h at 20 mm.
- Add a deck for every extra product; three decks make four fractions.
- Choose 2.4 m width for high tonnage, 1.0–1.6 m for sand and small plants.




IN THE PLANT

WHERE IT WORKS.

Inclined screens sit after the secondary and tertiary crushers, sizing the product into its sale fractions and returning the oversize to the crusher in closed circuit.

TYPICAL PLANT FLOW



BEHIND EVERY MACHINE

Field service

Installation, commissioning and inspection by GELEN engineers, on site anywhere we sell.

Spares by serial number

Every machine has a serial and a QR on its nameplate. Scan it, and its parts list, manuals and service history open – and a spares order is one tap away.

Remote support

Production data, alarms and performance analytics from every connected plant, with support from the works.

TALK TO THE WORKS.

ASO 1. OSB, Oğuz Cd. No: 31
06930 Sincan, Ankara, Türkiye

PHONE +90 312 267 06 20

E-MAIL gelenmakina@gelenmakina.com

WEB gelenmakina.com

Full specifications, drawings and every other GELEN machine are in the Products Catalogue.



SCAN FOR THE PRODUCT
PAGE, CATALOGUE AND
ENQUIRY FORM.



GELEN

CRUSHING & SCREENING PLANTS SINCE 1981

GELENMAKINA.COM